


PREMIUM

BISOL BIPV

Monocrystalline Roof Integrated PV Modules / BSO 370-380 Wp



Designed and
manufactured in EU



Replaces
conventional roof tiles



PID free



Limited shading



Module presorting
for higher profitability



Supremely low degradation



Module efficiency
up to 20.4 %




Up to 13 % higher
real-life performance




Excellent low light
performance


Guarantees:




I-V Curve at Various Irradiation Levels



I-V Curve at Various Cell Temperatures



Dimensions



Electrical Specifications @ STC (AM1.5, 1,000 W/m², 25 °C):

Module Type	BSO	370	375	380
Nominal Power	P_{MPP} [W]	370	375	380
Short Circuit Current	I_{SC} [A]	11.35	11.40	11.45
Open Circuit Voltage	V_{OC} [V]	41.6	41.9	42.1
MPP Current	I_{MPP} [A]	10.70	10.75	10.85
MPP Voltage	V_{MPP} [V]	34.6	34.9	35.0
Module Efficiency	η_M [%]	19.9	20.2	20.4
Power Output Tolerance		0/+5 W		
Maximum Reverse Current		20 A		
Protection Class		Class II		

Additional power classes available upon request. | Efficiency at irradiation 200 W/m²: 99.3 % of STC efficiency or higher. | Tolerances for V_{OC} and I_{SC} are 3 %.

Electrical Specifications @ NOCT (AM 1,5, 800 W / m², Wind: 1 m/s, Cell Temperature 44 °C):

Module Type	BSO	370	375	380
Nominal Power	P_{MPP} [W]	276.3	280.1	283.8
Short Circuit Current	I_{SC} [A]	9.18	9.22	9.26
Open Circuit Voltage	V_{OC} [V]	39.4	39.7	39.9
MPP Current	I_{MPP} [A]	8.66	8.70	8.78
MPP Voltage	V_{MPP} [V]	31.9	32.2	32.3

Power measurement tolerance: ± 3 %.

Thermal Specifications:

Current Temperature Coefficient	α	+ 0.06 %/C
Voltage Temperature Coefficient	β	- 0.27 %/C
Power Temperature Coefficient	γ	- 0.35 %/C
NOCT		44 \pm 2 °C
Temperature Range		- 40 °C to + 85 °C

Mechanical Specifications:

Length x Width x Thickness	1,813 mm x 1,075 mm x 25 mm
Weight	21 kg
Solar Cells	120 Half-Cut mono c-Si / 166 mm x 166 mm
Junction Box / Connectors	3 bypass diodes / MC4 compatible / IP 68
Frame	Solrif®
Cable Length	Default: 1,200 mm
Glass	3.2 mm glass with anti-reflective coating / tempered / high-transparency / low-iron content
Impact Resistance	Hailstone / Φ 25 mm / 83 km/h (51 mph)

Tolerances of values are ± 5 %. Unspecified product properties remain under full discretion of BISOL Production.

Packaging Information:

Modules per Pallet	Packing Dimension: Length/Width/Height	Stackable	Packing Weight	Tot. Nr. of Pallets/Load
24	196 x 116 x 119 cm	2 pallets	644 kg	26

Additional terms & conditions apply. Please see *Standard Limited Guarantee* and *General Sales Terms & Conditions*.

© BISOL Production Ltd. February 2022. All rights reserved. All information presented in this document is subject to change without prior notice and serve for informative purposes only.